

F-9820

S C a S a F Fa Ra

E E, A	
F l a	RF-9820S
F a	225-2600 MH
	13
C a a /Ba	25 H -40 M -e e

T L3Ha C a T a Ra
a - a a f
fa a a a a a .
T a , a -SWaP
a f ,
MANET a a
L -Of-S a a .T
RF-9820S a a a
L3Ha AN/PRC-163
M - a Ha a , a
a a a .

E, FACE	
Temperature	-22 F 131 F (-30 C +55 C)
Humidity	2 %
Shock	MIL-STD-810G
Vibration	MIL-STD-810H
Electromagnetic Interference	MIL-STD-461F

E, FACE	
Data	USB 2.0, IP e USB
Ports	19 ADF, A d , USB 2.0,
Connectors	50- TNC
Serial	USB 2.0
Power	OFF, ON, Z, 14 e e
Control	WebMMI

RF-9820S C. a. a. E. Fa. Ra.
 2022 L3Ha Tec e, I c. 03/2022 SP123C

Te Wae ad Te Wae Tec e, I c. ade a a e e eed ade a f Te Wae
 Tec e, I c. eU ed Sae ad e c e.

N. -E. C. I. a.
 L3Ha Tec e a a e ba ae ace ad defe e ec a , de e e d -e d
 a ee c e' -c ca eed. Tec a de ad a ced defe ea dc e ca
 ec e ac a , a d, ea, ace ad c be d a .